



PRODUCT DATA SHEET

FLEET PRO™ MONOGRADES **SAE 10W, 30, 40 & 50**

PRODUCT DESCRIPTION

FLEET PRO™ MONOGRADES are high performance heavy duty motor oils recommended for older four-stroke gasoline and diesel engines ¹.

FLEET PRO™ MONOGRADES meet the API service requirements of CF ², CF-2 ²/ SL and are formulated utilizing Group II base oils and the newest additive technology to provide outstanding protection for engines where these monograde viscosity is required by the OEM ³.

TECHNICAL DATA

(typical values)

SAE GRADE	ASTM	10W	30	40	50
Product Number		07-129010	07-129030	07-129040	07-129050
SDS Number		S051	S051	S051	S051
Viscosity @ 100°C, cSt	D445	5.66	11.99	14.18	19.05
API Gravity at 60°F	D1250	33.3	30.6	31.0	29.1
Pour Point, °C	D5950	-45	-36	-36	-33
Color ASTM	D1500	L2.5	L3.0	L3.0	3.0
CCS, cP	D5293	2,000 (-25°C)	NA	NA	NA
Flash Point COC, °C	D92	200	220	220	245

1. Always follow your operator's manual for recommended viscosity grade and API service classification
2. Obsolete specifications
3. Consult your owner's manual regarding its suitability for use in equipment from other OEMs

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

D0510816

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.