



# PRODUCT DATA SHEET

## NATIONAL™ FE MULTIVEHICLE ATF PREMIUM FULL SYNTHETIC

### PRODUCT DESCRIPTION

NATIONAL™ FE Multivehicle ATF is specifically formulated for the latest generation of high efficiency planetary gear transmissions. Use of synthetic base stocks provides additional oxidation control required for extended drain with excellent low temperature performance and fuel economy (FE). It provides extended protection to key performance aspects, including friction stability, clutch durability, oxidation resistance, wear control and corrosion control.

### TECHNICAL DATA

*(typical values)*

	ASTM	Typical
Product Number	07-001090	
SDS Number	S009.1	
Viscosity @ 100°C, cSt	D445	6.10
Viscosity @ 40°C, cSt	D445	30.65
Viscosity Index	D2270	151
API Gravity	Calc.	35.4
Pour Point, °C	D5950	-54
Brookfield @ -40°C, cP	D2983	13,500
Color ASTM	Visual	Red

### FEATURES

- ✓ Full synthetic formula
- ✓ Outstanding low temperature performance
- ✓ Improved torque transfer that promotes fuel economy
- ✓ Excellent oxidation and thermal stability

D0090415

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



# PRODUCT DATA SHEET

## APPLICATIONS (b) (c)

OEM / ATF	Application	OEM / ATF	Application
ATF	Shell 3353 Shell 134 Shell M-1375.4	Land Rover	P/N TYK5000050 P/N LR0022460
BMW / MINI	P/N 83 22 0 142 516 P/N 83 22 2152426 P/N 83 22 0 397 114 / 163 513	Maserati	P/N 231603
Chrysler / Dodge / Jeep	P/N 05127382AA P/N 68043742AA PN 68157995AA	Mazda	FZ
Mercedes / Daimler	MB 236.3/5/6/7/8/9	Mitsubishi	ATF-J3
Ford / Lincoln / Mercury	P/N XT-10-QLV [LV] (a) P/N XT-6-QSP or DSP [SP] (a)	Nissan / Infinity	Matic-S
GM / GMC / Opel / Saturn	AWI VI (a) P/N 88863400 P/N 88863401	Porsche	PN 000 043 304 00
Honda / Acura	DW-1	Saab	P/N 93 165 147 - AW-1
Hyundai / Kia	NWS-9638 T-5 P/N 040000C90SG SP-IV / SPH-IV	Toyota / Lexus / Scion	Type WS
Jaguar	Fluid 8432	Volkswagen / Audi	G 052 533 G 055 005 (-A, -A2) G 055 540 (A2) G 055 162 (A2/A6) G 060162 A1/A2/A6
JASO	M315, Class 1A		

(a) Products have different Brookfield and/ or viscosity requirements

(b) NATIONAL™ FE MULTIVEHICLE ATF (low viscosity) is suitable for most ATF's listed above however we are offering a fluid that have neither evaluated nor approved by vehicle manufacturers

(c) Consult your owner's manual regarding its suitability as ATF in imported vehicles. Do not use in ATF applications where CVT fluids or Ford ATF type F is required. Do not use in Honda power steering fluid systems

*This product is not for sale or use in the State of California*

D0090415

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8889 FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.