



PRODUCT DATA SHEET

NATIONAL™ FULL SYNTHETIC MULTIVEHICLE ATF

PRODUCT DESCRIPTION

National Full Synthetic Multi-Vehicle ATF offers extended friction control protection that lasts over the life of the fluid—long after the anti-shudder protection found in many competitive brands. Made with full synthetic base stocks, this ATF is inherently more thermally stable when compared with conventional base stocks.

National Full Synthetic Multi-Vehicle ATF is designed for use in most modern passenger vehicles and heavy duty applications. It also can be used in applications where its performance features exceed the requirements of older specifications.

FEATURES

- ✓ Full synthetic formula with outstanding low temperature performance
- ✓ Improved wear performance and reduced oil consumption
- ✓ Provides extended anti-shudder performance for smooth driving
- ✓ Excellent oxidation and thermal stability
- ✓ Exceeds the most demanding JASO 1A performance standard

D0081215

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



PRODUCT DATA SHEET

NATIONAL™ FULL SYNTHETIC MULTIVEHICLE ATF

TECHNICAL DATA

(typical values)

	ASTM	Typical
Product Number	07-001080	
SDS Number	S008.1	
Viscosity @ 100°C, cSt	D445	7.75
Viscosity @ 40°C, cSt	D445	37.28
Viscosity Index	D2270	184
API Gravity	Calc.	35.8
Pour Point, °C	D5950	-51
Brookfield @ -40°C, cP	D2983	12,000
Color ASTM	Visual	Red

APPLICATIONS (b) (c)

National Full Synthetic Multi-Vehicle ATF is specially formulated to exceed the performance and protection requirements of newer transmissions. Installers can rely on this single fluid to conveniently and accurately meet a wide array of global OEM requirements in North America:

D0081215

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



PRODUCT DATA SHEET

NATIONAL™ FULL SYNTHETIC MULTIVEHICLE ATF

OEM / ATF	Application	OEM / ATF	Application	OEM / ATF	Application
Allison	C4	GM/GMC/ Opel/Saturn	II/IID/IIE/IIIG/IIIH	Mazda	F-1
	TES-295 ^(a)		P/N 12378515 [Synthetic]		JWS3317
	TES-389		P/N 19 40 700		M-5, P/N XT-9-QMM5
ATF	EssoLT 71141	Honda/Acura Hyundai/Kia	P/N 19 40 767	Mitsubishi	M-III
	JWS 3309		P/N 21005966 Transaxle		Type T-IV
	Mobil ATF 3309		P/N 22717466		ATF-J2
	Shell 3403-M115		P/N 88900925	Nissan/Infiniti	SP, P/N MS991156
	Shell LA 2634		P/N 9986195		SP-II/III
	Texaco ETL 7045E		T-IV	Porsche	402
	Texaco ETL 8072B		Type A Suffix A		Matic-D/J/K/W
	Texaco N402		Z-1	PSA Peugeot Citroen Renault Saab SSANG YONG Subaru	P/N 000 043 204 41
Bentley	P/N Py112995PA	Hyundai/Kia	ATF Red-1K		P/N 000 043 205 09
	P/N 81 22 9 400 272/275		Genuine ATF		P/N 000 043 205 28
BMW/MINI	P/N 81 22 9 400 858/859	Idemitsu	JWS-3309 T-4	Suzuki	P/N 999 917 547 00 (A2)
	P/N 83 22 0 024 249/359		P/N UM040 CH20 Red-1		PSA Peugeot Citroen
	P/N 83 22 0 026 922	SP-II/III	Renault	Matic D2	
	P/N 83 22 0 402 413	ATF HP		Saab	3309-T-IV
	P/N 83 22 0 403 248	K17	SSANG YONG		DSIH 5M-66
	P/N 83 22 7 542 290	Isuzu		ATF II/III	Subaru
	P/N 83 22 9 407 765		Genuine ATF	P/N K0140Y0700	
	P/N 83 22 9 407 807	P/N 09200-9001	Jaguar	Fluid 8432	Toyota/Lexus/Scion
Chrysler/Dodge/ Jeep	+4 ^(a)	JLM 20238		Volkswagen/Audi	
	AS68RC ATF	JLM 20292	G 052 055		
	SP-III	JLM 21044	G 052 162 (-A1, -A2)		
Mercedes/Daimler	MB 236.3/5/6/7/8/9	K17	G 052 990 (A2)	Volvo	G 055 025 (A2)
	MB 236.10/11/91	WSS-M2C922-A1	G US 000 162		
Ford/Lincoln/ Mercury	P/N XT-2-QDX [M]	JASO	M315, Class 1A	Volvo	P/N 1161521
	P/N XT-2-QSM [Syn]		Land Rover		Esso Type LT 71141
	P/N XT-5-QM or -DM [V]	MAN		Texaco ETL 7045E	Volvo Const. Equip.
	P/N XT-8-QAW [Premium]		339A		
	P/N XT-9-QMM5 [FNR5]				
WSS-M2C922-A1					

- (a) Products have different Brookfield and/ or viscosity requirements
 - (b) NATIONAL™ FULL SYNTHETIC MULTIVEHICLE ATF (high viscosity) is suitable for most ATFs listed above however we are offering a fluid that have neither evaluated nor approved by vehicle manufacturers
 - (c) Consult your owner's manual regarding its suitability as ATF in imported vehicles. Do not use in ATF applications where CVT fluids or Ford ATF type F is required. Do not use in Honda power steering fluid systems
- This product is not for sale or use in the State of California*

D0081215

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.