



PRODUCT DATA SHEET

NATIONAL™ CONCRETE FORM OIL

PRODUCT DESCRIPTION

NATIONAL™ Concrete Form Oil is made with highly refined Group II base oils and special additives which is designed to wet metal and wood form materials to keep them clean with its excellent parting characteristics.

NATIONAL™ Concrete Form Oil may be brushed, sponged or sprayed on¹.

FEATURES :

- ✓ Rust and Oxidation protection to metal forms
- ✓ Clean separation forms
- ✓ Good cold temperature properties
- ✓ Sulfur and Zinc free mold release agents²

TECHNICAL DATA

(typical values)

ISO GRADE		22
Product Number		07-400100
SDS Number		S093
Viscosity @ 40°C, cSt	D445	21.28
API Gravity at 60°F	D1250	35.96
Pour Point, °C	D5950	-18
Flash Point, °C	D92	200
Copper Corrosion	D130	1A
Color ASTM	D1500	L0.5

- 1) Always apply it in a well ventilated area
- 2) With time additives tend to separate and drop to the bottom, please mix well before use

The recommended shelf life for these oils is typically 12 months from manufacturing date when stored properly in the original sealed containers.

D0930816

5009 WEST 81ST STREET | INDIANAPOLIS | INDIANA | 46268 | 800-829-8899 | FAX 317-875-0889

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes that the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.