



NATIONAL™ MERCON® LV/DEXRON® VI ATF | Transmission & Drive Train

Product Description

NATIONAL MERCON® LV/ DEXRON® VI is a high performance multi vehicle automatic transmission fluid formally approved by Ford and General Motors. It is also suitable for use in other low viscosity applications².

NATIONAL MERCON LV/ DEXRON® VI is formulated to meet the stringent viscometric, friction, wear and oxidation stability properties required in passenger car and light truck transmissions.

Approvals and Certifications

- **GM DEXRON® VI (License# J-62112):**
 - ◆ Back serviceable to prior generation GM applications; including DEXRON®-III, DEXRON®-II and Type A Suffix A
- **Ford MERCON® LV (License# MLV190803):**
 - ◆ It **cannot** be used in other Ford applications such as MERCON®, MERCON® SP, MERCON® V, and Type F applications
- **JASO M315-2015 1-A-LV15:**
 - ◆ For Japan Automaker Manufacturer Association applications

Features

- Outstanding low temperature performance and resistance against sludge and deposit formation
- Improved anti-wear protection which contributes to extended fluid life
- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



Technical Data (Typical Values)

	ASTM	Typical
Product Number	07-001066	
SDS Number	S145	
Viscosity @ 100°C, cSt	D445	5.8
Viscosity @ 40°C, cSt	D445	29.1
Viscosity Index	D2270	148
Specific Gravity 60°F	D4052	0.8477
Pour Point, °C	D5950	-54
Brookfield @ -40°C, cP	D2983	10,300
Color	Visual	Red

1. *Dexron® is a registered trademark of General Motors, LLC. Mercon® is a registered trademark of Ford Motor, Co.*
2. *Consult your owner's manual regarding its suitability as ATF in imported vehicles. Do not use in ATF applications where CVT fluids are required. Do not use in Honda power steering fluid systems.*

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

