



## MAJESTIC | Universal Tractor Hydraulic Fluid

---

### Product Description

MAJESTIC Universal Tractor Hydraulic Fluid (UTHF) is formulated with high quality base stocks, a shear stable viscosity index improver, oxidation and corrosion inhibitors, antifoaming agents, antiwear additives, and a pour point depressant to exceed the performance and protection requirements of tractors and other farm equipment used in North America.

### Features

- ✓ Excellent anti-wear capabilities
- ✓ EP & Load carrying capabilities
- ✓ One fluid does the job of a full range of tractor hydraulic systems
- ✓ Good compatibility with seals, O-rings, and packing materials maintains their good condition and keeps leakage at a minimum
- ✓ Oxidation and thermal stability
- ✓ Friction durability
- ✓ Protects against rust and corrosion of highly finished precision parts when operating in humid conditions and during seasonal shutdown periods
- ✓ Formulated to suppress brake “chatter” and transmission “slip” for quiet and efficient action of brakes and transmission

### Industry and OEM Applications <sup>1</sup>

- ◆ John Deere J20C
- ◆ Ford M2C86B, M2C86C, M2C134D
- ◆ Suitable for wet brakes
- ◆ API GL-4 <sup>2</sup>
- ◆ Suitable for hydraulic use

MAJESTIC UTHF is a multifunctional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

**AGCO:** 821XL, **Caterpillar:** TO-2, **Deutz-Allis Power Fluid:** 821XL, 25741, 25743, 246634, 272843, **Fiat Heston:** AF-87, **Ford:** FNHA-2-C-200, FNHA-2-C-201, ESN-M2C134A-D (NH-410B), ENS-M2C-77A, 78A, 79A, New Holland M4864A, **J.I. Case:** Case-O-Matic Type A, **John Deere:** J14A-C, J20A, J20B, J21A, JTD 303, **Kioti:** Tractor, **Landini:** Tractor, **Leyland for UTTO only:** Tractor, **Massey Ferguson:** 1103A&B, M1110, 1127, 1127A&B, M1129, M1129A (Permatran), M1135 (Permatran III), M1138, M1141, M1143, M1139 (STOU), M1144 (STOU), **Quatrol** (THF Brand), **Valmet:** Tractor, **Yanmar:** Tractor.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



## Technical Data

Product Number	07-392700	
SDS Number	S100	
Viscosity @ 100°C, cSt	D7279	10.57
Viscosity @ 40°C, cSt	D7279	72.19
Viscosity Index	D2270	133
Specific Gravity at 60°F	D4052	0.8705
Pour Point, °C	D5950	-39
Brookfield @ -35°C, cP	D2983	53,000
Color ASTM	D1500	L2.0

- 1) Consult your owner's manual regarding its suitability for use in equipment from other OEMs. This fluid performs in most equipment without concern for fluid-related harm. Additive producer applied engineering judgement to our data set and are confident that their additive can meet the performance requirements of the OEMs we have listed.
- 2) API GL-4 is an automotive gear lubricant specification, and this product is not recommended for use in hypoid applications.

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

