



NATIONAL | Universal Full Synthetic CVT Fluid

Product Description

NATIONAL Universal Full Synthetic CVT Fluid is formulated to meet the requirements of today's sophisticated continuously variable transmissions (CVT).

In addition, our full synthetic formula provides the friction performance, shear stability and durability needed in these applications for better fuel economy and efficiency of the vehicle during multiple driving cycles.

Features

- ✓ Full synthetic fluid
- ✓ Consistent friction performance under ranges of conditions
- ✓ Excellent anti-shudder durability
- ✓ Exceptional low temperature properties
- ✓ Oxidation and thermal stability
- ✓ Improved shear stability

Industry and OEM Applications ¹

NATIONAL Universal Full Synthetic CVT Fluid technology is recommended for use in CVT transmissions over a range of architectures and services:

Audi Multitronic; BMW/Mini Cooper: EZL 799/ 83220136376/ 83220429154, EZL/EZL 799A.ZF CVT V1; **Chery CVT;** **Daihatsu:** AMMIX CVTF DFE, CVT Fluid DC, CVT Fluid DFC, Fluid TC; **Dodge/Jeep/Chrysler:** NS-2, Mopar CVT+4; **Fiat:** Tutela Car CVT N.G; **Ford:** WSD-M2C-199A; **Fujijyuuko:** i-CVTF FG; **GM/Saturn:** DEX-CVT, GM1940713/ 1940714; **Honda:** Multimatic HMMF (without starting clutch), HCF2, Z-1 (CVT model, without starting clutch), CVT (not for use in any Honda with starting clutch); **Hyundai/Kia:** CVT-1, SP III (CVT model); **Idemitsu:** CVTF-EX1; **Lexus:** Fluid TC, Fluid FE; **Mazda:** JWS 3320, **MG Rover:** EM-CVT; **Mitsubishi:** CVTF-J1, CVTF-J4 and -J4+, SP-III (Diaqueen, CVT model only), CVTF ECO J4; **Nissan:** NS-1, -2, -3, N-CVT; **Punch CVT** (without starting clutch); **Renault:** Elf Matic CVT; **Shell Green 1V;** **Subaru:** iCVT, iCVT FG, ECVT, Lineartronic chain CVT and CVT II Fluid (K0425Y0710), Lineartronic High Torque (HT) CVT Fluid, CV-30 (K0421Y0700), NS-2; **Suzuki:** CVTF TC, CVTF 3320, CVTF 4401, NS-2, CVT Green 1, 2 & 1V; **Toyota:** CVTF TC, CVTF FE; **Volvo:** CVT 4959; **VW/Audi:** TL 521 16 (G 052 516), TL 521 80 (G 052 180).

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



Technical Data

| | | |
|--------------------------|-----------|--------|
| Product Number | 07-001095 | |
| SDS Number | S153 | |
| Viscosity @ 100°C, cSt | D7279 | 7.480 |
| Viscosity @ 40°C, cSt | D7279 | 35.67 |
| Viscosity Index | D2270 | 184 |
| Specific Gravity at 60°F | D4052 | 0.8456 |
| Pour Point, °C | D5950 | -48 |
| Brookfield @ -35°C, cP | D2983 | 11,400 |
| Color | Visual | Red |

- 1) Consult your owner's manual regarding its suitability for use in equipment from other OEMs. This fluid performs in most equipment without concern for fluid-related harm. Field performance was measured in multiple vehicles and have supporting data to demonstrate acceptable performance.
- 2) This product is not for sale or use in the State of California.

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

