

Product Data Sheet



AGRIPRO ARCTIC TRACTOR HYDRAULIC FLUID | Specialty Oils and Fluids

Product Description

AGRIPRO™ Arctic Tractor Hydraulic Fluid is formulated with the latest anti-wear and extreme pressure additives to provide exceptional protection against wear and scoring to help extend equipment life. AGRIPRO™ Arctic contains corrosion inhibitors to protect against rust and corrosion in wet or humid environments and has been specifically designed to ensure good low temperature fluidity in cold weather regions.

AGRIPRO™ Arctic delivers the varied lubricant performance properties required in severe duty applications of agriculture, forestry, mining and construction equipment drive trains. AGRIPRO™ Arctic carefully balanced formula is particularly well suited for reducing wet brake chatter.

INDUSTRY AND OEM APPLICATIONS^{1 3}:

- ◆ Vickers 35VQ25
- ◆ Caterpillar TO-2
- ◆ John Deere J20D
- ◆ Denison² HF-0, HF-1, HF-2 (pumps only)

FEATURES

- ✓ Excellent anti-wear capabilities
- ✓ EP & Load carrying capabilities
- ✓ Enhanced yellow metal protection
- ✓ Exceptional low temperature properties
- ✓ Oxidation and thermal stability
- ✓ Optimal friction properties
- ✓ Improved shear stability resulting in extended drain intervals

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



AGRIPRO ARCTIC TRACTOR HYDRAULIC FLUID | Specialty Oils and Fluids

Technical Data

(typical values)

ASTM		
Product Number		07-120800
SDS Number		S055
Viscosity @ 100°C, cSt	D445	7.67
Viscosity @ 40°C, cSt	D445	34.44
Viscosity Index	D2270	202
API Gravity @60°F	D1250	33.2
Pour Point, °C	D5950	-54
Brookfield @ -40°C, cP	D2983	13,600
Color	D1500	L3.0

1) These are additive approvals for "Service Fill" applications. Additive producer applied engineering judgement to our data set and are confident that their additive can meet the performance requirements of the OEMs we have listed

2) Will not satisfy the Denison demulsibility requirements

3) Consult your owner's manual regarding its suitability for use in equipment from other OEMs. This fluid performs in most equipment without concern for fluid-related harm.

The recommended shelf life for these oils is typically 36 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



Pinnacle Oil Toll Free: 1-800-829-8899 | Tel: 1-317-875-9465 |

www.PinnacleOil.com